



SYCOR
TECHNOLOGY INC.

Braid

Tinned Copper Tubular Braid



Sycor Part Number	QQ-B-575 Part Number	Nominal Inside Diamete	Wire Size AWG	Number Of Wires	Braid Size AWG	Circula MIL Area	Approx. Weight Lbs./Mft.
A0C24136TT	QQB575R36T031	.031"	36	24	22	600	2
A0C24236TT	QQB575R36T062	.062"	36	48	19	1,200	4
A0C16234TT	QQB575R34T062	.062"	34	32	19	1,351	4.3
A0C16132TT	QQB575R32T062	.062"	32	16	20	1,011	3.3
A0C24336TT	QQB575R36T078	.078"	36	72	18	1,800	6
A0C24436TT	QQB575R36T109	.109"	36	96	16	2,400	8.2
A0C16434TT	QQB575R34T109	.109"	34	64	16	2,544	8.8
A0C16232TT	QQB575R32T109	.109"	32	32	17	2,023	6.6
A0C24536TT	QQB575R36T125	.125"	36	120	15	3,000	10.3
A0C24334TT	QQB575R34T125	.125"	34	72	16	2,862	9.2
A0C24232TT	QQB575R32T125	.125"	32	48	15	3,034	10.1
A0C241036TT	QQB575R36T156	.156"	36	240	12	6,000	20.9
A0C24736TT	QQB575R36T171	.171"	36	168	14	4,200	14.3
A0C24534TT	QQB575R34T171	.171"	34	120	13	4,770	15.6
A0C24332TT	QQB575R32T171	.171"	32	72	14	4,551	14.7
A0C241336TT	QQB575R36T203	.203"	36	312	11	7,800	28
A0C24834TT	QQB575R34T203	.203"	34	192	11	7,632	27.9
A0C24532TT	QQB575R32T203	.203"	32	120	11	7,585	24.6
A0C241636TT	QQB575R36T250	.250"	36	384	10	9,600	34.5
A0C24530TT	QQB575R30T281	.281"	30	120	9	12,000	42
A0C48836TT	QQB575R36T375	.375"	36	384	10	9,600	34.5

Federal Specification QQ-B-575
TT= Tinned Tubular

Sycor Advance Wire and Cable