



SYCOR
TECHNOLOGY INC.

Automotive Wire

Type GPT- Lighting & Primary Wire

Sycor Part Number	Size AWG	Stranding	Insulation Thickness In Inches	Nominal O.D. In Inches	Approximate Weight Lbs/M Ft.
A1S2002	20	7/.0126	.023"	.086"	9.1
A1S2010	20	10/.0100	.023"	.086"	9.1
A1S1816	18	16/.0100	.023"	.095"	12.5
A1S1619	18	19/.0113	.023"	.105"	16.5
A1S1619	16	19/.0113	.023"	.105"	16.1
A1S1419	14	19/.0142	.023"	.19"	24.0
A1S1219	12	19/.0179	.026"	.144"	36.7
A1S1019	10	19/.0226	.031"	.178"	58.3
A1S0819	8	19/.0295	.037"	.226"	97.6
A1S0874	8	74/.0142	.037"	.218"	88.4
A1S06133	6	133/27	.043"	.281"	114.0

CONSTRUCTION:

Stranded copper conductors with PVC insulation.

TEMPERATURE:

-40°C to 80°C

INSULATION:

PVC

APPLICATION:

For use whenever SAE J-1128 specifies general circuit wiring.

COLOUR:

Available in solid colours and stripes, with optional custom printing and/or numbering.

SPECIFICATIONS:

Meets Ford spec. (M1L-56A), and Chrysler (MS-3450).

Sycor Technology - Advance Wire and Cable Division
2455 Milltower Court, Mississauga, Ontario - L5N-5Z6
Phone: (905)821-3591, Fax: (905)821-7260

Sycor Advance Wire and Cable