



SYCOR
TECHNOLOGY INC.

Communication and Control Cable Shielded Intercom Cable



CONSTRUCTION:

Solid bare copper conductors, colour coded Polyvinyl Chloride insulated pairs twisted together, overall Polyvinyl Chloride jacket, tinned copper drain wire and an aluminum mylar shield.

APPLICATION:

For installation of communication systems.

APPROVALS:

Certified to CSA standard C22.2 No. 2 14 as PCC Communications Cable.
Listed as UL Type CM as per subject 444.
Passes UL 70,000 BTU flame test.
Passes CSA FT-4 vertical flame test.

Sycor Part Number	# of Pairs	Size AWG	Strandin	D.C.R. ohms/100 Meters	Nominal O.D. In Inches
	1	22	Solid	53.15	.131"
	2	22	Solid	53.15	.182"
	3	22	Solid	53.15	.193"
	4	22	Solid	53.15	.211"
	6	22	Solid	53.15	.239"
	9	22	Solid	53.15	.281"

COLOUR CODE CHART

1	White paired with Blue
2	White paired with Orange
3	White paired with Green
4	White paired with Brown
5	White paired with Grey
6	Red paired with Blue
7	Red paired with Orange
8	Red paired with Green
9	Red paired with Brown

