



SYCOR

TECHNOLOGY INC.

Communication and Control Cable Intercom Cable



CONSTRUCTION:

Solid, copper conductors, colour coded Polyvinyl Chloride insulation and overall Polyvinyl Chloride jacket.

APPLICATION:

For installation of communication systems.

APPROVALS:

Certified to CSA standard C22.2 No. 214 as PCC Communications Cable.
Listed as UL Type CM as per subject 444.
Passes UL 70,000 BTU flame test.
Passes CSA FT-4 vertical flame test.

COLOUR CODE CHART:

A

Sycor Part Number	# of Pairs	Size AWG	Strandin	Nom. Insulatio Thicknes	Nom. Jacket Thicknes	Nomina O.D. In Inches
SY22101	1	22	Solid	.006"	.020"	.133"
SY22102	2	22	Solid	.006"	.020"	.182"
SY22103	3	22	Solid	.006"	.020"	.193"
SY22104	4	22	Solid	.006"	.020"	.210"
SY22106	6	22	Solid	.006"	.020"	.238"
SY22108	8	22	Solid	.006"	.020"	.273"
SY22109	9	22	Solid	.006"	.020"	.277"
SY22110	10	22	Solid	.006"	.020"	.289"
SY22111	11	22	Solid	.006"	.020"	.289"
SY22112	12	22	Solid	.006"	.020"	.304"
SY22113	13	22	Solid	.006"	.020"	.310"
SY22115	15	22	Solid	.006"	.020"	.328"
SY22116	16	22	Solid	.006"	.020"	.350"
SY22118	18	22	Solid	.006"	.020"	.364"
SY22120	20	22	Solid	.006"	.020"	.374"
SY22121	21	22	Solid	.006"	.020"	.389"
SY22123	23	22	Solid	.006"	.020"	.397"
SY22125	25	22	Solid	.006"	.025"	.407"
SY22126	26	22	Solid	.006"	.025"	.417"
SY22130	30	22	Solid	.006"	.025"	.450"
SY22131	31	22	Solid	.006"	.025"	.450"
SY22050	50	22	Solid	.006"	.040"	.630"
SY22100	100	22	Solid	.006"	.040"	.850"

VALUE ADDED SERVICES

Cutting & Stripping, Cable & Harness Assembly, Custom Colouring, Striping, Bonding, Round to Flat Lamination, Tin Dipping, Re-spooling

Sycor Technology Inc. Advance Wire and Cable Division

2455 Milltower Court, Mississauga, Ontario L5N 5Z6 Phone: (905) 821-3591, Fax: (905) 821-7260

Sycor Advance Wire and Cable