



SYCOR
TECHNOLOGY INC.

Communication and Control Cable

Multi-Conductor Foil Shield



CONSTRUCTION:

Stranded tinned copper conductors, colour coded Polyethylene insulation, Polyvinyl Chloride jacket overall. 100% foil shield and stranded tinned copper drain wire.

TEMPERATURE RATING:

-20°C to 80°C

VOLTAGE RATING:

600 Volts

JACKET COLOUR:

Grey

COLOUR CODE:

1 - Black 3 - Red
2 - Clear 4 - Green

APPLICATION:

Audio cable

APPROVAL:

CSA FT-4
UL Approved

Sycor Part Number	# of Con	Size AWG	Strand	Size of Drain Wire	Insul. Thick. In Inches	Nom. Jacke Thick. Inches	Nom. O.D.	Nom. Cap. pF/Ft. A B	Weigh #/Mft
H2A0222	2	22	7/30	24	.015"	.023"	.175"	24 47	18
H2A0322	3	22	7/30	24	.015"	.023"	.184"	24 47	22
H2A0422	4	22	7/30	24	.015"	.023"	.200"	24 47	28
H2A0220	2	20	10/30	22	.015"	.023"	.187"	27 49	22
H2A0320	3	20	10/30	22	.015"	.023"	.197"	27 49	28
H2A0420	4	20	10/30	22	.015"	.023"	.216"	27 49	34
H2A0218	2	18	16/30	20	.015"	.023"	.210"	24 46	30
H2A0318	3	18	16/30	20	.015"	.023"	.222"	24 46	38
H2A0418	4	18	16/30	20	.015"	.023"	.242"	24 46	46
H2A0216	2	16	26/30	18	.015"	.023"	.236"	27 49	40
H2A0316	3	16	26/30	18	.030"	.030"	.329"	27 49	68
H2A0416	4	16	26/30	18	.030"	.030"	.360"	27 49	82
H2A0214	2	14	41/30	16	.030"	.030"	.338"	31 56	70
H2A0314	3	14	41/30	16	.030"	.030"	.359"	31 56	90
H2A0414	4	14	41/30	16	.030"	.030"	.394"	31 56	112
H2A0212	2	12	65/30	14	.030"	.030"	.402"	35 63	100
H2A0312	3	12	65/30	14	.030"	.030"	.430"	35 63	134
H2A0412	4	12	65/30	14	.030"	.030"	.473"	35 63	166

VALUE ADDED SERVICES

Cutting & Stripping, Cable & Harness Assembly, Custom Colouring, Striping, Bonding, Round to Flat Lamination, Tin Dipping, Re-spooling,

In this catalogue we have included a wide variety of wire & cable products. However, there are many more available. If the product you require is not shown here, contact your Sycor Representative.

Short Run Custom Designed Cables For Prototypes and Engineering Runs

Sycor Advance Wire and Cable