



SYCOR

TECHNOLOGY INC.

Ribbon Cable

.050" Centre Colour Coded Bonded Ribbon Cable

UL Approved, 105°C, 300 Volts



APPROVALS:

UL Style 2693

CONDUCTOR:

Tinned Copper

VOLTAGERATING:

300 Volts

TEMPERATURE RATING:

105°C

COLOUR:

Any combination of colours can be bonded to meet your requirements.

VALUE ADDED SERVICES

Cutting & Stripping
Terminating, Tin Dipping

Sycor Part Number	AWG	Number of Conductor	Strandin	Nominal Width	Approx. Weight Lbs./CFT.
PIG3010T-CC	30	10	7/38	0.32"	0.74
PIG3015T-CC	30	15	7/38	0.48"	1.11
PIG3020T-CC	30	20	7/38	0.64"	1.48
PIG3030T-CC	30	30	7/38	0.96"	2.22
PIG2810T-CC	28	10	7/36	0.35"	1.00
PIG2815T-CC	28	15	7/36	0.53"	1.50
PIG2820T-CC	28	20	7/36	0.70"	2.00
PIG2830T-CC	28	30	7/36	1.05"	3.00
PIG2610T-CC	26	10	7/34	0.39"	1.42
PIG2614T-CC	26	14	7/34	0.55"	1.99
PIG2615T-CC	26	15	7/34	0.59"	2.13
PIG2616T-CC	26	16	7/34	0.63"	3.18
PIG2620T-CC	26	20	7/34	0.78"	2.84
PIG2630T-CC	26	30	7/34	1.17"	4.26
PIG2410T-CC	24	10	7/32	0.44"	2.05
PIG2415T-CC	24	15	7/32	0.66"	3.08
PIG2420T-CC	24	20	7/32	0.88"	4.10
PIG2430T-CC	24	30	7/32	1.32"	6.15
PIG2210T-CC	22	10	7/30	0.51"	2.97
PIG2215T-CC	22	15	7/30	0.77"	4.46
PIG2220T-CC	22	20	7/30	1.02"	5.94
PIG2230T-CC	22	30	7/30	1.53"	8.91

The cables described in the above chart are our more popular combinations however Sycor can provide an infinite number of combinations. Contact your Sycor representative for details.

In this catalogue we have included a wide variety of wire & cable products. However, there are many more available. If the product you require is not shown here, contact your Sycor Representative.

Sycor Advance Wire and Cable