




SYCOR
TECHNOLOGY INC.

Portable Cord

Type SJ



CONSTRUCTION:

Flexible stranded copper conductors with separator and colour coded insulation. Cabled with filler, separator, and overall rubber jacket. UL & CSA listed.

TEMPERATURE RATING:

60°C

VOLTAGE RATING:

300 Volts
AMPS per NEC Art. 400

INSULATION:

Rubber

JACKET:

Rubber

APPLICATION:

Extra hard usage, portable lights, battery chargers, portable stage lights, heavy tools and equipment.

COLD BEND:

Meets UL cold bend test at -40°C

JACKET COLOUR:

Black

Sycor Part Number	No. of Con	Size AWG	Strand	Insul. Thick.	Jack Thick.	O.D.	Amp	Approx Weight Lbs./Mf
SJ182	2	18	16 x 30	.030"	.030"	.291"	10	49
SJ183	3	18	16 x 30	.030"	.030"	.310"	10	64
SJ184	4	18	16 x 30	.030"	.030"	.340"	7	74
SJ162	2	16	26 x 30	.030"	.030"	.312"	13	60
SJ163	3	16	26 x 30	.030"	.030"	.331"	13	77
SJ164	4	16	26 x 30	.030"	.030"	.367"	10	95
SJ142	2	14	41 x 30	.030"	.030"	.344"	18	73
SJ143	3	14	41 x 30	.030"	.030"	.367"	18	97
SJ144	4	14	41 x 30	.030"	.030"	.405"	15	120
SJ122	2	12	65 x 30	.030"	.045"	.416"	25	108
SJ123	3	12	65 x 60	.030"	.045"	.440"	25	136
SJ124	4	12	65 x 30	.030"	.045"	.483"	20	180
SJ102	2	10	104 x 30	.045"	.060"	.572"	30	200
SJ103	3	10	104 x 30	.045"	.060"	.601"	30	244
SJ104	4	10	104 x 30	.045"	.060"	.660"	25	306
Constant Service - Flexible Stranding								
SJ182F	2	18	41 x 34	.030"	.030"	.291"	10	49
SJ183F	3	18	41 x 34	.030"	.030"	.310"	10	64
SJ184F	4	18	41 x 34	.030"	.030"	.340"	7	74
SJ162F	2	16	65 x 34	.030"	.030"	.312"	13	54
SJ163F	3	16	65 x 34	.030"	.030"	.331"	13	77
SJ164F	4	16	65 x 34	.030"	.030"	.367"	10	93

Sycor Advance Wire and Cable