




SYCOR
TECHNOLOGY INC.

Portable Cord

Type SJT



CONSTRUCTION:

Extra flexible stranded copper conductors with separator and colour coded thermoplastic insulation. Cabled with filler, separator, and overall thermoplastic jacket. UL & CSA listed.

TEMPERATURE RATING:

60°C or 105°C

VOLTAGE RATING:

300 Volts
AMPS per NEC Art. 400

INSULATION:

Polyvinyl Chloride

JACKET:

Polyvinyl Chloride

APPLICATION:

For electric mixer, polishers, washing machines and portable appliance. Flexible stranding for continuous service.

JACKET COLOUR:

Black

COLD BEND:

Meets UL cold bend test at -35°C

Sycor Part Number	No. of Con	Size AWG	Strand	Insul. Thick	Jack Thick	O.D.	Amp	Approx Weight Lbs./Mf
Stationary Service - 60°C								
SJT182-60	2	18	16 x 30	.030"	.030"	.293"	10	49
SJT183-60	3	18	16 x 30	.030"	.030"	.312"	10	38
SJT162-60	2	16	26 x 30	.030"	.030"	.314"	13	56
SJT163-60	3	16	26 x 30	.030"	.030"	.334"	13	72
Constant Service - 105°C - Extra Flexible Stranding								
SJT182-105	2	18	41 x 34	.030"	.030"	.293"	10	49
SJT183-105	3	18	41 x 34	.030"	.030"	.312"	10	58

Sycor Advance Wire and Cable