



SYCOR
TECHNOLOGY INC.

Automotive Wire

Type TWP - Primary Wire - Thin Wall



CONSTRUCTION:

Stranded copper conductors with Polyvinyl Chloride insulation.

TEMPERATURE RATING:

-40°C to 90°C

INSULATION:

Polyvinyl Chloride

APPLICATION:

Where small diameter and minimal weight is desirable. For use in SAE J-1560 applications.

COLOUR:

Available in solid colours and stripes, with optional custom printing and/or numbering.

SPECIFICATIONS:

Meets Ford spec. (MIL-120A), and Chrysler (MS-7889).

Sycor Part Number	Size AWG	Strand	Nominal Insulation Thickness	Nominal O.D.	Approx Weight Lbs./Mf
	22	7/30	.016"	.062"	3.6
	20	7/28	.016"	.070"	5.2
	18	16/30	.016"	.078"	6.9
	16	19/29	.016"	.089"	10.0
	14	19/27	.016"	.103"	14.4
	12	19/25	.018"	.126"	22.0

Value Added Services

Cutting & Stripping, Cable & Harness Assembly, Custom Colouring, Striping, Bonding, Round to Flat Lamination, Tin-Dipping, Re-spooling, Printing

Sycor Advance Wire and Cable