



**SYCOR**  
TECHNOLOGY INC.

## Welding Cable Hypalon® Jacketed



### DESCRIPTION:

Flexible Welding Cable,  
Resistant to tearing, abrasion,  
oils, gasoline and greases.

### CONDUCTOR:

6 AWG through 4/0 Class K  
stranded annealed bare copper

### JACKET:

Black Hypalon®

### TEMPERATURE RATING:

-25°C to +75°C

### VOLTAGE RATING:

600 Volts

### APPLICATION:

For connections from electrode holder and  
clamp to arc welder, bus welding box or  
transformers. Useful in applications where  
high flexibility is required.

Sycor Part Number	No. of Cond.	Size AWG	Strand.	Nom. O.D.	Approx. Weight Lbs/Mft.
G8B06259B	1	6	259	.370"	135
G8B04413B	1	4	413	.420"	188
G8B02665B	1	2	665	.500"	300
G8B01840B	1	1	840	.580"	364
G8B1/01064B	1	1/0	1064	.620"	452
G8B2/01330B	1	2/0	1330	.670"	526
G8B3/01653B	1	3/0	1653	.720"	702
G8B4/02107B	1	4/0	2107	.810"	842

© Registered DuPonttrademark

**Sycor Technology Inc.** Advance Wire and Cable Division  
2455 Milltower Court, Mississauga, Ontario L5N 5Z6 Phone: (905) 821-3591, Fax: (905) 821-7260

Sycor Advance Wire and Cable