



Silver Plated Copper Tubular Braid

Description

Tubular braided wire with silver plated copper may be used when exposed to high temperatures or where corrosion resistance is necessary. It comes in a variety of widths and constructions and is most often used for wire protection against physical damage or to shield wires from signal interference.

Approvals

A-A-59569
(Supercedes QQ-B 575)
Copper Strand(s) meet(s) ASTM B3 (Bare), B33(Tinned)

Construction

Uninsulated, soft drawn solid silver plated copper conductors woven or braided into a tubular configuration

Application

Silver plated tubular braid may be used for flexible ground connections, wire shielding with temperatures exceeding 200°C and provides better corrosion resistance than tinned copper



Sycor Part #	QQ-B-575 Part Number	Nominal Inside Diameter	Braid Size AWG	Construction			Number Of Wires	Circular MIL Area	Approx. Weight Lbs./Mft.
				Std per Carrier	# of carriers	AWG of Strand			
AOC24136ST	QQB575/A-A59569R36S031	.031	22	24	1	36	24	600	2
AOC24236ST	QQB575/A-A59569R36S062	.062	19	24	2	36	48	1,200	4
AOC16234ST	QQB575/A-A59569R34S062	.062	19	16	2	34	32	1,351	4.3
AOC16132ST	QQB575/A-A59569R32S062	.062	20	16	1	32	16	1,011	3.3
AOC24336ST	QQB575/A-A59569R36S078	.078	18	24	3	36	72	1,800	6
AOC24436ST	QQB575/A-A59569R36S109	.109	16	24	4	36	96	2,400	8.2
AOC16434ST	QQB575/A-A59569R34S109	.109	16	16	4	34	64	2,544	8.8
AOC16232ST	QQB575/A-A59569R32S109	.109	17	16	2	32	32	2,023	6.6
AOC24536ST	QQB575/A-A59569R36S125	.125	15	24	5	36	120	3,000	10.3
AOC24334ST	QQB575/A-A59569R34S125	.125	16	24	3	34	72	2,862	9.2
AOC24232ST	QQB575/A-A59569R32S125	.125	15	24	2	32	48	3,034	10.1
AOC241036ST	QQB575/A-A59569R36S156	.156	12	24	10	36	240	6,000	20.9
AOC24736ST	QQB575/A-A59569R36S171	.171	14	24	7	36	168	4,200	14.3
AOC24534ST	QQB575/A-A59569R34S171	.171	13	24	5	34	120	4,770	15.6
AOC24332ST	QQB575/A-A59569R32S171	.171	14	24	3	32	72	4,551	14.7
AOC241336ST	QQB575/A-A59569R36S203	.203	11	24	13	36	312	7,800	28
AOC24834ST	QQB575/A-A59569R34S203	.203	11	24	8	34	192	7,632	27.9
AOC24532ST	QQB575/A-A59569R32S203	.203	11	24	5	32	120	7,585	24.6
AOC241636ST	QQB575/A-A59569R36S250	.250	10	24	16	36	384	9,600	34.5
AOC24530ST	QQB575/A-A59569R30S281	.281	9	24	5	30	120	12,000	42
AOC48836ST	QQB575/A-A59569R36S375	.375	10	48	8	36	384	9,600	34.5

Additional configurations may be available upon request. Please contact us to enquire. You may also be interested in tin plated tubular braid or nickel plated tubular braid.

Value Added Services



Cutting



Re-Spooling



Terminating



Ground Straps



Tin Dipping

Sycor Technology Inc., 1-2220 Argentia Road, Mississauga ON L5N 2K7

www.sycor.com 1-800-268-9444 sales@sycor.com

Sycor International Inc ©All Rights Reserved