



Tinned Copper Tubular Braid

Description

Tubular braided wire comes in both tinned and bare copper. It comes in a variety of widths and constructions and is most often used for wire protection against physical damage or to shield wires from signal interference.

Construction

Uninsulated, soft drawn bare or tinned copper conductors woven or braided into a tubular configuration



Approvals

A-A-59569
(Supersedes QQ-B 575)
Copper Strand(s) meet(s) ASTM B3 (Bare), B33(Tinned)

Application

Tubular braid may be used for flexible ground connections, wire shielding



Sycor Part #	QQ-B-575 Part Number	Braid Size AWG	Construction			Nominal Inside Diameter	Number Of Wires	Circular MIL Area	Approx. Weight Lbs./Mft.
			Std per Carrier	# of carriers	AWG of Strand				
A0C24136TT	QQB575/A-A59569R36T031	22	24	1	36	.031	24	600	2
A0C24236TT	QQB575/A-A59569R36T062	19	24	2	36	.062	48	1,200	4
A0C16234TT	QQB575/A-A59569R34T062	19	16	2	34	.062	32	1,351	4.3
A0C16132TT	QQB575/A-A59569R32T062	20	16	1	32	.062	16	1,011	3.3
A0C24336TT	QQB575/A-A59569R36T078	18	24	3	36	.078	72	1,800	6
A0C24436TT	QQB575/A-A59569R36T109	16	24	4	36	.109	96	2,400	8.2
A0C16434TT	QQB575/A-A59569R34T109	16	16	4	34	.109	64	2,544	8.8
A0C16232TT	QQB575/A-A59569R32T109	17	16	2	32	.109	32	2,023	6.6
A0C24536TT	QQB575/A-A59569R36T125	15	24	5	36	.125	120	3,000	10.3
A0C24334TT	QQB575/A-A59569R34T125	16	24	3	34	.125	72	2,862	9.2
A0C24232TT	QQB575/A-A59569R32T125	15	24	2	32	.125	48	3,034	10.1
A0C241036TT	QQB575/A-A59569R36T156	12	24	10	36	.156	240	6,000	20.9
A0C24736TT	QQB575/A-A59569R36T171	14	24	7	36	.171	168	4,200	14.3
A0C24534TT	QQB575/A-A59569R34T171	13	24	5	34	.171	120	4,770	15.6
A0C24332TT	QQB575/A-A59569R32T171	14	24	3	32	.171	72	4,551	14.7
A0C241336TT	QQB575/A-A59569R36T203	11	24	13	36	.203	312	7,800	28
A0C24834TT	QQB575/A-A59569R34T203	11	24	8	34	.203	192	7,632	27.9
A0C24532TT	QQB575/A-A59569R32T203	11	24	5	32	.203	120	7,585	24.6
A0C241636TT	QQB575/A-A59569R36T250	10	24	16	36	.250	384	9,600	34.5
A0C24530TT	QQB575/A-A59569R30T281	9	24	5	30	.281	120	12,000	42
A0C48836TT	QQB575/A-A59569R36T375	10	48	8	36	.375	384	9,600	34.5

Replace the suffix TT with BT for bare copper.

Additional configurations may be available upon request. Please contact us to enquire.

You may also be interested in silver plated tubular braid or nickel plated tubular braid.

Value Added Services



Cutting



Re-Spooling



Terminating



Ground Strap



Tin Dipping

Sycor Technology Inc., 1-2220 Argentia Road, Mississauga ON L5N 2K7

www.sycor.com 1-800-268-9444 sales@sycor.com

Sycor International Inc ©All Rights Reserved