



# Kynar Heat shrink Tubing

## Description

Sycor's Kynar (PVDF) heat shrink tubing uses shrinkable Polyvinylidene fluoride that's semi rigid. Kynar Tubing is flame retardant and has amazing resistance to industrial chemicals, fuels and fluids that can be harmful.

## Approvals

UL 224 VW-1  
CSA OFT  
MIL-DTL-23053/8  
(Man products are dual/tri-rated)

## Construction

Polyvinylidene Fluoride (PVDF) Tubing

## Temperature Rating

-55°C to +175°C  
*Shrinks at:* 175°C

## Voltage Rating

CSA/UL 600 Volts

## Application

Sycor's Kynar heat shrinkable tubing is useful for applications that involve bundling wires, wire repair or insulation, jacketing, and protection of in-line components. Kynar tubing offers high flexibility and strength.

## Shrink Ratio

2:1



Sycor Number	NOM Size	Unshrunk Diameter	shrunk Diameter	Standard Spool put-ups		Lbs/100'
				Bulk	Shop	
TOM.046	3/64"	1.2mm	0.6mm	200mm	25	0.03
TOM.062	1/16"	1.6mm	0.8mm	200mm	25	0.05
TOM.093	3/32"	2.4mm	1.2mm	200mm	25	0.06
TOM.125	1/8"	3.2mm	1.6mm	200mm	25	0.07
TOM.187	3/16"	4.8mm	2.4mm	200mm	25	0.1
TOM.250	1/4"	6.4mm	3.2mm	200mm	25	0.15
TOM.375	3/8"	9.5mm	4.7mm	200mm	25	0.25
TOM.500	1/2"	12.7mm	6.4mm	100mm	25	0.3
TOM.750	3/4"	19.1mm	9.5mm	50mm	25	0.5
TOM1.00	1"	25.6mm	12.7mm	20mm	25	0.8

## Options/Notes



\*Available in various spool lengths or sticks

## Value Added Services



Cutting

## Color Codes



Sycor Technology Inc., 1-2220 Argentia Road, Mississauga ON L5N 2K7

[www.sycor.com](http://www.sycor.com) 1-800-268-9444 [sales@sycor.com](mailto:sales@sycor.com)

Sycor International Inc ©All Rights Reserved