

RG #	SHIELD(S)	DIELECTRIC	GAUGE (AWG)	NOM. IMP. (OHMS)	NOM. O.D	APPROVAL
59/U	100% ALUMINUM FOIL 40% B.C BRAID	PE	22 SOLID B.C	75	0.242"	NONE
59/U	100% ALUMINUM FOIL 4x28 AWG DRAIN WIRES	PE	22 SOLID COPPERWELD	80	0.242"	CSA FT1
59/U	95% B.C BRAID	PE	22 AWG, 7 STR. B.C.	75	0.242"	CSA FT1
59/U	70% B.C BRAID	PE	22 SOLID COPPERWELD	75	0.242"	CSA FT1
59/U	95% B.C BRAID	PE	22 SOLID COPPERWELD	80	0.242"	CSA FT1
					0.242"	CSA FT4
59/U	95% B.C BRAID	PE	22 SOLID B.C	80	0.242"	CSA FT1
					0.242"	CSA FT4
59B/U	95% B.C BRAID	PE	23 SOLID COPPERWELD	75	0.242"	CSA FT1
59/U	100% ALUMINUM FOIL 40% ALUMINUM BRAID	PE	20 SOLID COPPERWELD	75	0.242"	CSA FT4
59/U - VIDEO	98% DBL T.C BRAID	PE	20 SOLID B.C	75	0.305"	CSA FT1
					0.305"	CSA FT4
59/U - DUAL COND.	95% B.C BRAID (DUAL)	PE	2 X SOLID COPPERWELD	75	0.238" x 0.478"	CSA FT1
59/U OUTDOOR	95% B.C BRAID	PE	22 SOLID COPPERWELD	80	0.242"	CSA FT1
59/U OUTDOOR W/MESSENGER	95% B.C BRAID	PE	22 SOLID COPPERWELD	80	0.394" x 0.242"	CSA FT1