



CSA AWM, UL Style 10086, ETFE (Tefzel)

Description

Solid or stranded tin or silver plated copper conductor with ETFE (Ethylene Tetrafluoroethylene) insulation.

Approvals

CSA AWM FT-1
UL Style 10086

Construction

Stranded tinned copper conductors
Optional silver-plated or nickel-plated conductors
Tefzel® (Ethylene tetrafluoroethylene) (ETFE) insulation

Temperature Rating

CSA/UL: 200°C

Voltage Rating

CSA/UL: 600 Volts

Application

Used in electronic and appliance applications where higher continuous use temperatures potentially exist.

Alternative Product

M22759/16 150°C 600V



Sycor Part No	Size AWG	Stranding	Nominal Insulation Thick.		Nominal O.D (in)		Approx. Weight	
			inches	mm	inches	mm	lbs/1000ft	kg/km
A0H2407T	24	7/32	0.010	0.3	0.044	1.1	2	3
A0H2419T	24	19/36	0.010	0.3	0.044	1.1	3	4
A0H2207T	22	7/30	0.010	0.3	0.050	1.3	3	4
A0H2219T	22	19/34	0.010	0.3	0.050	1.3	3	4
A0H2007T	20	7/28	0.010	0.3	0.058	1.5	5	7
A0H2019T	20	19/32	0.010	0.3	0.058	1.5	5	7
A0H1801T	18	Solid	0.010	0.3	0.060	1.5	6	9
A0H1807T	18	7/26	0.010	0.3	0.068	1.7	6	9
A0H1607T	16	7/0.192	0.010	0.3	0.078	2.0	10	15
A0H1619T	16	19/.0117	0.010	0.3	0.079	2.0	9.77	15
A0H1626T	16	16/26	0.010	0.3	0.077	2.0	12	18
A0H1401T	14	Solid	0.010	0.3	0.084	2.1	14	21
A0H1407T	14	7/.0242	0.010	0.3	0.092	2.3	15	22
A0H1419T	14	19/27	0.010	0.3	0.089	2.3	15	22
A0H1219T	12	19/25	0.015	0.4	0.119	3.0	23	34
A0H1037T	10	37/26	0.015	0.4	0.145	3.7	38	57
A0H10105T	10	105/30	0.015	0.4	0.154	3.9	38	57
A0H0819T	8	19/.0295	0.025	0.6	0.191	4.9	61	91
A0H0619T	6	19/.0372	0.025	0.6	0.231	5.9	93	138



Colours

Stock colours 0-9. Custom colors and striped combinations available upon request.

Colour Codes



Value Added Services



Cutting



Twisting



Re-Spooling



Terminating

Sycor Technology Inc., 1-2220 Argentia Road, Mississauga ON L5N 2K7

www.sycor.com 1-800-268-9444 sales@sycor.com

Sycor International Inc ©All Rights Reserved