



KYNAR® Back Panel Wire Wrap

CSA 105°C, 150 Volts

Description

Solid, silver plated "Kynar": insulated conductors for solderless wire wrap applications.

Approvals

CSA PVF-2
UL 1422, UL 1423, UL 1327

Construction

Solid silver-plated copper conductor
Kynar® (Polyvinylidene Fluoride)(PVF) insulation

Temperature Rating

UL/CSA - 105°C

Voltage Rating:

Not Specified - 150 - 600 Volts



Application:

Back panel wire wrap may be used in computer and business machine applications, however only in applications that are not subject to movement or mechanical damage.

Alternative Product

Mil Spec M81822/3 135°C 300V
Mil Spec M81044/12 150°C 600V for extruded Kynar® insulation



Sycor Part No	Size AWG	Stranding	Insulation Thick. (in)	Conductor Diameter (in)	UL Style Number
A0E3001S	30	Solid	.0045	.020	1423
A0E2801S	28	Solid	.0055	.024	1422
A0E2601S	26	Solid	.0055	.027	1422
A0E2401S	24	Solid	.0045	.030	1423
A0E2201S	22	Solid	.0110	.025	1327
A0E2001S	20	Solid	.0110	.032	1327

Additional strandings and gauges available upon request.

Color

Stock colors 0-9. Custom colors and striped combinations available upon request.

Value Added Services



Cutting



Re-Spooling



Terminating



Twisting

Color codes



Sycor Technology Inc., 1-2220 Argentia Road, Mississauga ON L5N 2K7

www.sycor.com 1-800-268-9444 sales@sycor.com

Sycor International Inc ©All Rights Reserved