



Types SPT-1 & SPT-2 Parallel Lamp Cord

Description

Sycor's Type SPT-1 & SPT-2 are intended for household appliances, but are still very durable being oil, water, acid, Ozone and alkalis resistant.

Construction

Annealed, bunch stranded copper per UL 62.
Polyvinylchloride (PVC) per UL 62.

Application:

For use in household appliances, including clocks, fans and radios as well as lamps.

Approvals

CSA and UL approved

Temperature Rating

-60°C to +105°C

Voltage Rating

300 Volts



Sycor Part No	No of Cond.	AWG	Stranding	Insulation Thick.	O.D.	Approx Weight Lbs./Mft.
SPT1						
SPT1 182-60B	2	18	41/34	.030	.105x198	19
SPT1 182-105B	2	18	41/34	.030	.105x198	19
SPT1 182-105T	2	18	41/34	.030	.105x.198	19
SPT1 182-60T	2	18	41/34	.030	.105x.198	19
SPT-2						
SPT2 182-105B	2	18	41/34	.045	.135x25.5	27

Color Codes



Value Added Services



Cutting

Re-Spooling

Terminating

Sycor Technology Inc., 1-2220 Argentia Road, Mississauga ON L5N 2K7

www.sycor.com 1-800-268-9444 sales@sycor.com

Sycor International Inc ©All Rights Reserved