



# Flat Festoon Cable

## Description

Flat Festoon Cable is a type of flat cable designed for use in festoon systems, for power and control on cranes and hoists. It is used where there is space restrictions and where extreme flexing is required. Festoon Cable has a bend radius of 3-5 times its diameter. It is suitable for indoor or outdoor use. It is oil resistant and operates well in low temperature conditions. Temperature ratings range from -40 to 105°C.

## Construction

Flat festoon is made with stranded bare copper conductors, available with either a PVC jacket or with a rubber (EPR/Neoprene) jacket, and comes in various gauge sizes and conductor counts.

## Approvals


CSA , UL, or CE/HAR available

## Temperature Rating

PVC 105°C, Neoprene 90°C

## Voltage Rating:

CSA & UL 600 Volts CE/HAR  
450/500V



*For more information or a quote on festoon cable, please contact us to enquire*

## Color

Standard colors 0-9.

## Color Codes



## Value Added Services



Cutting



Re-Spooling



Terminating

Sycor Technology Inc., 1-2220 Argentia Road, Mississauga ON L5N 2K7

[www.sycor.com](http://www.sycor.com) 1-800-268-9444 [sales@sycor.com](mailto:sales@sycor.com)

Sycor International Inc ©All Rights Reserved