



MIL-W-16878/19, Type DN

115°C, 3000 Volts

Description

PVC/Nylon insulated hook-up wire.

Temperature Rating

NEMA -55°C to 105°C

Approvals

MIL-W-16878/19 Type DN
SAE/NEMA HP-7

Voltage Rating:

3000 Volts



Construction

Stranded tinned copper conductor
Polyvinyl Chloride (PVC) insulation
Clear nylon jacket

Application:

Internal wiring of electrical and electronic equipment.

Sycor Part No	Size AWG	Stranding	Insulation Thickness	Jacket Thickness	Nominal O.D.	Approx Weight Lbs./M ft.
A2H2407T	24	7/32	.030	.003	.092	5.33
A2H2207T	22	7/30	.030	.003	.099	6.44
A2H2007T	20	7/28	.030	.003	.106	8.21
A2H1807T	18	7/26	.030	.003	.116	10.92
A2H1619T	16	19/29	.030	.004	.128	13.51
A2H1419T	14	19/27	.030	.004	.142	18.59
A2H1219T	12	19/25	.030	.004	.168	28.94
A2H1037T	10	37/26	.030	.004	.192	41.38

Value Added Services



Cutting



Striping



Re-Spooling



Terminating

*Additional strandings and gauges available upon request. Please contact us to enquire.
May be available with silver plated conductor rated to 105°C.*

Color

Stock colors 0-9. Custom colors and striped combinations available upon request.

Color codes

