



Automotive Wire

Type GPT – Lighting & Primary Wire

Construction

Stranded bare copper conductors
Polyvinyl Chloride (PVC) insulation

Approvals:

Meets Ford spec(M1L-56A) and Chrysler (MS-3450)

Temperature Rating

-40°C to +80°C

Application

For use whenever SAE J-1128 specifies general circuit wiring



Sycor Part No	Size AWG	Stranding	Insulation Thickness	Nominal O.D.	Approx Weight Lbs./Mft.	SAE	Ford	Chrysler
A1S2007	20	7/.0126	.023	.086	9.1	J-1128	M1L-56A	MS-3450
A1S1816	18	16/.0100	.023	.095	12.5	J-1128	M1L-56A	MS-3450
A1S1619	16	19/.0113	.023	.105	16.1	J-1128	M1L-56A	MS-3450
A1S1419	14	19/.0142	.023	.19	24.0	J-1128	M1L-56A	MS-3450
A1S1219	12	19/.0179	.026	.144	36.7	J-1128	M1L-56A	MS-3450
A1S1019	10	19/.0226	.031	.178	58.3	J-1128	M1L-56A	MS-3450
A1S0819	8	19/.0295	.037	.226	97.6	J-1128	M1L-56A	MS-3450
A1S0874	8	74/.0142	.037	.218	88.4	J-1128	M1L-56A	MS-3450

*Tinned copper conductor may be available on a special order basis. Please contact us to enquire.

Value Added Services



Cutting



Stripping



Re-spooling



Terminating



Printing



Twisting

Color codes



Color

Stock colors 0-9. Custom colors and striped combinations available upon request.

Sycor Technology Inc., 1-2220 Argentia Road, Mississauga ON L5N 2K7

www.sycor.com 1-800-268-9444 sales@sycor.com

Sycor International Inc ©All Rights Reserved