



# Automotive Wire

## Type HDT – Lighting & Primary Wire-Heavy Wall

### Construction

Stranded bare copper conductors.  
Polyvinyl Chloride (PVC) insulation

### Temperature Rating

-40°C to 80°C

### Application

For use in applications where greater physical protection is required.

### Approvals

Meets Ford spec(M1L-50A) and Chrysler (MS-3490)



Sycor Part No	Size AWG	Stranding	Insulation Thickness	Nominal O.D.	Approx Weight Lbs./Mft.	SAE	Ford	Chrysler
HDT2007B	20	7/28	.036	.111	8.6	J-1128	M1L-50A	MS-3490
HDT1816B	18	16/30	.037	.123	11.0	J-1128	M1L-50A	MS-3490
HDT1619B	16	19/29	.040	.138	15.0	J-1128	M1L-50A	MS-3490
HDT1419B	14	19/27	.041	.154	20.0	J-1128	M1L-50A	MS-3490
HDT1219B	12	19/25	.046	.183	30.0	J-1128	M1L-50A	MS-3490
HDT1019B	10	19/23	.046	.206	43.0	J-1128	M1L-50A	MS-3490
HDT0819B	8	19/21	.055	.254	67.0	J-1128	M1L-50A	MS-3490

\*Tinned copper conductor may be available on a special order basis. Please contact us to enquire.

### Color codes



### Value Added Services



Cutting



Stripping



Re-Spooling



Terminating



Printing



Twisting

Sycor Technology Inc., 1-2220 Argentia Road, Mississauga ON L5N 2K7

[www.sycor.com](http://www.sycor.com) 1-800-268-9444 [sales@sycor.com](mailto:sales@sycor.com)

Sycor International Inc ©All Rights Reserved